




Artikelnummer/Itemnumber: 11277VG

Tarifnummer Export: 73084000 | Frachtkategorie: A

Geländerpfosten aus Ø 48er Standrohr

Railing post made of Ø48 mm round tube



Artikelbeschreibung:

für den Einsatz als Absturzsicherung, mit 3 angeschweißten Bügeln (Innenmaß: 65 x 170 mm) zum Einhängen von Brettern
Höhe: 1,00 m Überflur geeignet für faltgerüstbock System S 1200, faltgerüstbock Universal, sowie alle Kurbel-Gerüstböcke

Verwendungszweck:

Für den Einsatz bei Arbeiten im Hochbau

Technische Daten:

Gewicht: 3,70 kg/St
Material :
S235 JR

Oberfläche:
Feuerverzinkt nach DIN ISO 1461

item description:

for use as fall protection, with 3 welded-on brackets (inner dimension: 65 x 170 mm) for hanging boards, stand tube made of Ø 48.3 mm round tube, with welded pipe socket for insertion into sleeve made of Ø 48,3 mm round tube. Height: 1.00 m above ground suitable for folding jack system, folding jack Universal, as well as all crank-operated scaffolding jacks

designated purpose:

For the application for work in building construction

technical specifications:

weight: 3,70 kg/pc
material:
S235 JR

surface:
hot dipped galvanized

*Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen lediglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten o.ä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.
*All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.