



Artikelnummer/Itemnumber: 113112

Tarifnummer Export: 73181900 | Frachtkategorie: A

Rollgewindestab Ø 15mm x 6200mm, roh, Länge: 1200 mm

Threaded rod Ø 15 mm x 6200 mm, untreated, Length: 1200 mm



Artikelbeschreibung:

Rollgewindestab Ø 15 mm x 6200 mm
gerolltes Gewinde, biegsam, Pzul. 85 kN, alle Längen in
roh und verzinkter
Ausführung lieferbar. Gebrauchslast 85 kN, Bruchlast
170 kN, Außenmaß 17 mm,
Kernmaß 15 mm, Steigung 10 mm, Länge: 6,20 m, roh,
Länge: 1200 mm

Verwendungszweck:

Für den Einsatz bei Arbeiten im Hochbau

Technische Daten:

Gewicht: 1,80 kg/St
Material:
S235 JR

Oberfläche:
roh

item description:

Threaded rod Ø 15 mm x 6200 mm
threaded rod, bendable, Pperm. 85 kN, all length
available untreated or galvanized.
Service load 85 kN, ultimate load 170 kN, outside
dimension 17 mm,
core dimension 15 mm, pitch 10 mm; length: 6.20m,
untreated, Length: 1200 mm

designated purpose:

For the application for work in building construction

technical specifications:

weight: 1,80 kg/pc
material:
S235 JR

surface:
raw material

*Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen lediglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten o.ä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.
*All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.