



Artikelnummer/Itemnumber: 4072FUH+1

Tarifnummer Export: 73269098 | Frachtkategorie: A

Edelstahlpfosten Ø 76 mm ohne Ziernut, umlegbar, selbsteinrastende Verriegelung zum Einbetonieren, mit feuerverzinkter Bodenhülse Typ 470.60, ca. 400 mm Unterflur, mit Dreikantverschluss nach DIN 3223, mit 1

Stainless steel post Ø 76 mm without decorative ring, foldable, self-engaging lock for casting in concrete, with hot-dip galvanized ground socket part-no. 470.60, approx. 400 mm below ground, with triangular locking



Artikelbeschreibung:

Edelstahlpfosten Ø 76 mm
Überflur ca. 900 mm, umlegbar, selbsteinrastende Verriegelung
zum Einbetonieren, mit feuerverzinkter Bodenhülse Typ 470.60, ca. 400 mm Unterflur, mit Dreikantverschluss nach DIN 3223, mit 1 Öse

item description:

Stainless steel post Ø 76 mm
above ground approx. 900 mm
Ø 76 mm Ground, foldable, self-engaging lock
for casting in concrete, with hot-dip galvanized ground socket part-no. 470.60, approx. 400 mm below ground, with triangular locking mechanism acc. with DIN 3223, with 1 eyelet

Technische Daten:

Gewicht: 8,50 kg/St

technical specifications:

weight: 8,50 kg/pc

*Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen lediglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten o.ä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.

*All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.