




Artikelnummer/Itemnumber: 465B+2

Tarifnummer Export: 73269098 | Frachtkategorie: A1

Absperr-Stilpfosten, Serie 465B, Ø 60 mm, Gesamtlänge ca. 1400 mm, ohne Verschluss, mit 2 Ösen

Ornamental bollard, Series 465B, Ø 60 mm, total length approx. 1400 mm, without lock, with 2 eyelets



Artikelbeschreibung:

Die Absperr-Stilpfosten-Serie Ø 60 mm, ist eine leichte, aber dennoch schmuckvolle Variante unserer Stilpoller. Absperr-Stilpfosten aus Stahlrundrohr, Ø 60 mm, ca. 950 mm Überflur, feuerverzinkt und anthrazitgrau (RAL 7016) beschichtet, ortsfest, zum Einbetonieren, mit Erdanker, Gesamtlänge ca. 1400 mm, ohne Verschluss, mit 2 Ösen

item description:

The ornamental bollard series Ø 60 mm, a light-weight but very stylish version of our ornamental bollards. Barrier ornamental bollard of round steel tube, Ø 60 mm, approx. 950 mm above ground, hot-dip galvanized and coated anthracite grey (RAL 7016), stationary, for casting in concrete, with ground anchor, total length approx. 1400 mm, without lock, with 2 eyelets

Technische Daten:

Gewicht: 5,50 kg/St
Material:
S235 JR

Oberfläche:
feuerverzinkt und anthrazitgrau (RAL 7016) beschichtet

technical specifications:

weight: 5,50 kg/pc
material:
S235 JR

surface:
hot-dip galvanized and coated anthracite grey (RAL 7016)

*Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen lediglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten oä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.

*All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.