




Artikelnummer/Itemnumber: 482FUHB+2

Tarifnummer Export: 73269098 | Frachtkategorie: A1

Absperr-Stilpfosten, Serie 482B, Ø 82 mm, mit feuerverzinkter Bodenhülse Typ 470.60, ca. 400 mm Unterflur, mit Dreikantverschluss, mit 2 Ösen

Ornamental bollard, Series 482B, Ø 82 mm, with hot-dip galvanized ground socket part-no. 470.60, approx. 400 mm below ground, with triangular locking mechanism, with 2 eyelets



Artikelbeschreibung:

Stilpoller aus Stahlrundrohr Ø 82 mm, ca. 900 mm Überflur, feuerverzinkt und beschichtet, Farbe: DB703, umlegbar, selbststeinrastende Verriegelung, zum Einbetonieren, mit feuerverzinkter Bodenhülse Typ 470.60, ca. 400 mm Unterflur, mit Dreikantverschluss nach DIN 3223, mit 2 Ösen

item description:

Ornamental bollard of round steel tube Ø 82 mm, approx. 900 mm above ground, hot-dip galvanized and coated, color: DB703, foldable, self-engaging lock, for casting in concrete, with hot-dip galvanized ground socket part-no. 470.60, approx. 400 mm below ground, with triangular locking mechanism acc. with DIN 3223, with 2 eyelets

Technische Daten:

Gewicht: 13,00 kg/St

Material:
S235 JR

Oberfläche:
Feuerverzinkt und Pulverbeschichtet

technical specifications:

weight: 13,00 kg/pc

material:
S235 JR

surface:
hot dipped galvanized and powder coated

*Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen lediglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten o.ä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.

*All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.