




Artikelnummer/Itemnumber: 491B

Tarifnummer Export: 73269098 | Frachtkategorie: A

Absperrpfosten, Stahlrohr Ø 102 x 2,9 mm, ortsfest, zum Einbetonieren, feuerverzinkt und weiß beschichtet mit drei rot reflektierenden Leuchtstreifen

Barrier posts, steel tube Ø 102 x 2,9 mm, stationary, for casting in concrete, hot-dip galvanized and white coated with three red reflecting stripes



Artikelbeschreibung:

Absperrpfosten, Stahlrohr Ø 102 x 2,9 mm, mit aufgeschweißter Stahlkappe, 900 mm Überflur, ortsfest, zum Einbetonieren, mit Erdanker, Gesamtlänge: ca. 1300 mm, feuerverzinkt und weiß beschichtet mit drei rot reflektierenden Leuchtstreifen, ohne Öse

item description:

Barrier posts, steel tube Ø 102 x 2,9 mm, with welded steel cap, 900 mm above ground, stationary, for casting in concrete, with ground anchor, total length: 1300 mm, hot-dip galvanized and white coated with three red reflecting stripes, without eyelet

Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

designated purpose:

For stopping, and securing or saving of areas.

Technische Daten:

Gewicht: 10,00 kg/St
Material:
S235 JR

technical specifications:

weight: 10,00 kg/pc
material:
S235 JR

Oberfläche:
Feuerverzinkung nach DIN ISO 1461

surface:
hot dipped galvanized acc. to DIN ISO 1461

*Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen lediglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten oä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.

*All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.