

Lynlåsmuffe med lim

3:1 med lim - WAC

- Materiale: Polyolefin med lim
- Kryppefaktor: 3:1
- Krympetemperatur: 120°C
- Temperatur område: -55°C til 110°C
- Godkendelser: ASTM, ISO, UL
- Gennemslagsspænding: 12 kV/mm



Best. nr.	Type	Kabeldiameter Ø i mm (D/d)	Godstykkelse fuldt krympet (S)	Længde i mm
204152	WAC-mini/250	34/10	3,0	250
204008	WAC-0/250	50/15	3,0	250
204015	WAC-1/250	75/22	3,0	250
204022	WAC-2/250	105/30	3,0	250
204039	WAC-3/250	146/30	3,0	250
204046	WAC-4/250	188/55	3,0	250
204169	WAC-mini/500	34/10	3,0	500
204053	WAC-0/500	50/15	3,0	500
204060	WAC-1/500	75/22	3,0	500
204077	WAC-2/500	105/30	3,0	500
204084	WAC-3/500	146/30	3,0	500
204091	WAC-4/500	188/55	3,0	500
204176	WAC-mini/1000	34/10	3,0	1000
204107	WAC-0/1000	50/15	3,0	1000
204114	WAC-1/1000	75/22	3,0	1000
204121	WAC-2/1000	105/30	3,0	1000
204138	WAC-3/1000	146/30	3,0	1000
204145	WAC-4/1000	188/55	3,0	1000

CERTIFICERING:

